



aplicaCer Capagruesa Blanco or Gris

CEMENT-BASED TILE ADHESIVE FOR
INDOOR THICK-SET TILING

Cement-based adhesive for laying indoor tiles of
medium/high absorption using the thick-set method

- Thick-set adhesive
- Apply directly onto bricks
- 20 mm thickness

DESCRIPTION

White or grey cement-based adhesive used for levelling out surfaces and tiling directly on top of brickwork or concrete blocks.

APPLICATIONS

Tiling indoor floors and finishes using ceramic tiles of medium/high porosity, for formats smaller than 45 x 45 cm.

Thick-set application (up to 20 mm).

APPLICATION SURFACES

Conventional surfaces, brickwork, cement-based mortar floors and finishes. The application surface must be hard, perfectly set and free from dust, paint, oil, etc.

WARNINGS AND RECOMMENDATIONS

- For plaster surfaces, use **aplicaCer Especial Yeso**.
- For formats larger than 45 x 45 cm, use **aplicaCer Capagruesa Extra**.
- Do not apply this product when frost is forecasted.
- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply in areas where there is a risk of standing water.
- In high temperatures, windy conditions or if the application surface is very absorbent, it is advisable to moisten the surface and wait for the film of water to disappear before applying the product.
- Check that the paste is sticky enough by periodically lifting one of the tiles already in place to ensure that it is well stuck down.
- Use within 1 year of date of packaging. Store the product in its original packaging in a dry, covered place protected from humidity.

INSTRUCTIONS FOR USE



- 1 Add water and mix by hand or mechanically until you obtain a smooth paste of a workable consistency. Leave the paste to stand for 5 minutes and mix again before applying.
- 2 Apply using the traditional tiling method, with a thick coat over the whole area. If double gluing is required, spread the mixture over the back of the tile as well.
- 3 Put the ceramic tiles on top of the freshly-laid adhesive, pressing lightly to ensure that the whole tile surface comes into contact with the adhesive, filling any grooves.
- 4 Leave a joint of a width of at least 1.5 mm between indoor tiles. Wait 24 hours before grouting wall tiles and 48 hours before grouting floor tiles.
- 5 Respect all perimeter and structural joints. Place one partition joint every 50 m² on indoor floors.

aplicaCer Capagruesa Blanco or Gris

CEMENT-BASED TILE ADHESIVE
FOR INDOOR THICK-SET TILING

AVAILABLE FORMATS

aplicaCer Capagruesa Blanco or Gris is available in 25 kg paper sacks with moistureproof plastic lining, dispatched on shrink-wrapped pallets weighing a total of 1,600 kg (64 sacks).



TECHNICAL FEATURES

Appearance	Grey or white powder	Adhesive strength after 28 days	$\geq 0,5 \text{ N/mm}^2$
Mixing Water	4, 3-4,8 l/sack	Yield	15 - 16 kg/m ²
Paste Density	1,8 kg/l	Thickness (max)	20 mm
Paste life	2 hours		

Data based on tests carried out under normal laboratory conditions $23 \pm 2^\circ\text{C}$ and $50 \pm 5\% \text{HR}$ < 0.2 m/s

NOTE

The recommendations for use are based on our own knowledge and experience. The technical data provided have been obtained under normal laboratory conditions, and may therefore vary according to the environmental conditions in the place where the product is used. As the application conditions are beyond our control, the information provided here does not imply that the company accepts responsibility for any variations.