



# aplicaRev Igualador

ACRYLIC PAINT THAT PERFORMS  
AS A LEVELLER OF COLOURED  
FINISHING RENDERING MORTARS

- Acrylic Coating
- Rainproof
- Permeable to water vapor
- Resistant to alkalinity

## DESCRIPTION

Water-based, acrylic, waterproofing coating for the protection and decoration of façades or for indoor use.

## USES

Excellent leveller of coloured finishing rendering mortars, which suffer colour shade variations. These may be caused by differences in coating thickness, application surface's reflexion, adverse weather conditions during application, unfavourable curing conditions, etc.

## PROPERTIES

- Rainproof.
- Permeable to water vapor, allowing transpiration of the application surface.
- Weatherproof.
- High opacity.
- Resistant to the alkalinity of the application surface (cement-based mortars, concrete...).
- Good adhesion on usual application surfaces.

## APPLICATION SURFACES

The application surface to be painted must be hard, flat, clean, dry, free from dust, grease, salt, traces of paint, mold, and algae.

Wait until fully set and dry of the base render.

Make sure that on painted surfaces the old paint is in good condition and well adhered.

## INSTRUCTIONS FOR USE



- 1 Shake well before using until complete homogenization of the product.
- 2 Apply by brush, roller or spray.
- 3 We recommend applying two coats for better waterproofing and protection of the façade. First coat: Dilute paint with approximately 15-20 % of drinking water. Second coat: Product must be applied neat or diluted with a 5-10 % of water.

## WARNINGS AND RECOMMENDATIONS

- It is not recommended to paint in rainy weather, when there is a strong wind or during the hottest hours of the day in summer.
- The surface temperature must be a minimum of +8°C and a maximum of +35°C. Relative humidity should not exceed 80%.
- Protect containers from extreme temperatures, exposure to direct sunlight and frost.
- All tools must be washed with clean water immediately after use. Once hardened, the material can only be removed mechanically.
- Waste disposal in an authorized collection point.

# aplicaRev Igualador

ACRYLIC PAINT THAT PERFORMS AS A LEVELLER OF  
COLOURED FINISHING RENDERING MORTARS

## AVAILABLE FORMATS

**aplicaRev Igualador** is available in a plastic container of 15 litres (24 kg).  
Storage: up to 12 months in its original packaging in a cool, dry place. Keep tightly closed.

## TECHNICAL FEATURES

Colours	The same ones as aplicaRev Monocapa RM
Appearance	Matt paint
Solvent	Water
Viscosity	150-200 poises (Brookfield RTV to 20°C, Sp.6, 20)
Density	1,6 ± 0,1 Kg/litre
Solids Volume	46%
Gardner washability	>10.000 cycles (UNE 48.284)
Tensile strength	1,26 N/mm <sup>2</sup> (UNE EN 1542:2000)
Liquid water permeability	W=0,09 Kg/m <sup>2</sup> *h <sup>0.5</sup> Low (UNE EN 1062-3)
Water vapor permeability	Sd: 0,2 m Medium (UNE EN ISO 7783-2)
Accelerated aging	Unchanged
Yield	6 - 8 m <sup>2</sup> / litre and coat
Drying	Tacking: 30 minutes. Recoat: 4-6 hours. Total: 15-20 days

## NOTE

The recommendations for use are based on our own knowledge and experience. The technical data provided have been obtained under normal laboratory conditions, and may therefore vary according to the environmental conditions in the place where the product is used. As the application conditions are beyond our control, the information provided here does not imply that the company accepts responsibility for any variations.