

APLICACER CAPAGRUESA GRAN FORMATO CE

Cement-based adhesive for laying indoor tiles of medium/high absorption



Specially formulated for use on large format walls



Adhesive for indoor use

DESCRIPTION

Grey or white cement-based adhesive, classified as an adhesive for indoor use according to Standard UNE-EN 12004.

APPLICATIONS

Tiling indoor floors and finishes using ceramic tiles of medium/high porosity, applying thicknesses of up to 15 mm. Especially suitable for large format tiling. A double glue technique should be used for tiles larger than 30 cm x 30 cm.

APPLICATION SURFACES

Conventional surfaces, large format, cement-based mortar floors and finishes. The application surface must be hard, perfectly set and free from dust, paint, oil, etc.

MODO DE EMPLEO



1. Add water and mix by hand or mechanically until you obtain a smooth paste of a workable consistency.
2. Leave the paste to stand for 5 minutes and mix again before applying.
3. Spread the paste on the surface in sections of a surface area no larger than 2 m², combing with a suitable trowel. If double gluing is required, spread the mixture over the back of the tile as well.
4. Put the ceramic tiles on top of the freshly-laid adhesive, pressing lightly to ensure that the whole tile surface comes into contact with the adhesive, filling any grooves.
5. Leave a joint of a width of at least 1.5 mm between indoor tiles. Wait 24 hours before grouting wall tiles and 48 hours before grouting floor tiles.
6. Respect all perimeter and structural joints. Place one partition joint every 50 m² on indoor floors.

APLICACER CAPAGRUESA GRAN FORMATO CE

Rev - 07/2024

WARNINGS AND RECOMMENDATIONS

- For formats larger than 45 x 45 cm, use aplicaCer Capa Gruesa Extra.
- Do not apply this product when frost or rain are forecasted.
- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply in areas where there is a risk of standing water.
- In extreme weather conditions (wind or high temperatures), the product will dry more quickly than usual. This will result in a shorter open time.
- In high temperatures, windy conditions or if the application surface is very absorbent, it is advisable to moisten the surface and wait for the film of water to disappear before applying the product.
- Check, periodically, that a surface film has not formed on the adhesive paste once it has been spread onto the surface. If a film has formed, remove the product and apply a fresh coat.
- Check that the paste is sticky enough by periodically lifting one of the tiles already in place to ensure that it is well stuck down.
- Use within 1 year of date of packaging. Store the product in its original packaging in a dry, covered place protected from humidity.

AVAILABLE FORMATS

aplicaCer Capa Gruesa Gran Formato CE is available in 25 kg papersacks with moisture-proof plastic lining, dispatched on shrink-wrapped pallets weighing a total of 1,600 kg (64 sacks).

TECHNICAL FEATURES

Appearance	White or grwy powder
Powder density	4,3-4,8 l/sack
Paste Density	1,8 Kg/l
Paste life	2 hours
Adhesive strength after normal conditions	≥ 0,5 N/mm ²
Adhesive strength after water cycle	≥ 0,5 N/mm ²
Yield	15-16 Kg/m ²
Thickness (max.)	20 mm

Data based on tests carried out under normal laboratory conditions 23 ±2°C and 50 ± 5%HR <0,2 m/s

NOTE

The recommendations for use are based on our own knowledge and experience. The technical data provided have been obtained under normal laboratory conditions, and may therefore vary according to the environmental conditions in the place where the product is used. As the application conditions are beyond our control, the information provided here does not imply that the company accepts responsibility for any variations.