

APLICACER

Blanco/Gris CE

CEMENT-BASED TILE ADHESIVE FOR INDOOR USE
Cement-based adhesive for laying indoor tiles of medium/high absorption.



Adhesive for indoor use



High-porosity tiles



Excellent workability

DESCRIPTION

White/grey cement-based adhesive, classified as an adhesive for indoor use according to Standard UNE-EN 12004.

APPLICATIONS

Tiling indoor floors and finishes using ceramic tiles of medium/high porosity (> 3%). A double glue technique should be used for tiles larger than 30 cm x 30 cm.

SURFACES

Conventional surfaces and cement-based mortar floors and finishes. The application surface must be hard, perfectly set and free from dust, paint, oil, etc.

INSTRUCTIONS FOR USE

1. Add water and mix by hand or mechanically until you obtain a smooth paste of a workable consistency.
2. Leave the paste to stand for 5 minutes and mix again before applying.
3. Spread the paste on the surface in sections of a surface area no larger than 2 m², combing with a suitable trowel. If double gluing is required, spread the mixture over the back of the tile as well.
4. Put the ceramic tiles on top of the freshly-laid adhesive, pressing lightly to ensure that the whole tile surface comes into contact with the adhesive, filling any grooves.
5. Leave a joint of a width of at least 1.5 mm between indoor tiles. Wait 24 hours before grouting wall tiles and 48 hours before grouting floor tiles.
6. Respect all perimeter and structural joints. Place one partition joint every 50 m² on indoor floors.



APLICACER Blanco/Gris CE

Rev - 07/2024

WARNINGS AND RECOMMENDATIONS

- For plaster surfaces, use aplicaCer Especial Yeso.
- For formats larger than 40 x 40 cm, we recommend using aplicaCer Exteriores.
- Do not apply this product when frost is forecasted.
- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply in areas where there is a risk of standing water.
- In extreme weather conditions (wind or high temperatures), the product will dry more quickly than usual. This will result in a shorter open time.
- In high temperatures, windy conditions or if the application surface is very absorbent, it is advisable to moisten the surface and wait for the film of water to disappear before applying the product.
- Check, periodically, that a surface film has not formed on the adhesive paste once it has been spread onto the surface. If a film has formed, remove the product and apply a fresh coat.
- Check that the paste is sticky enough by periodically lifting one of the tiles already in place to ensure that it is well stuck down.
- Use within 1 year of date of packaging. Store the product in its original packaging in a dry, covered place protected from humidity.

AVAILABLE FORMATS

aplicaCer Blanco/Gris CE is available in 25 kg paper sacks with moisture-proof plastic lining, dispatched on shrink-wrapped pallets weighing a total of 1,600 kg (64 sacks) and 20 kg paper sacks on pallets of 1.280 kg.

TECHNICAL FEATURES

Appearance	Grey or white powder
Grain size	<1 mm
Powder density	1,4 Kg/l
Mixing water	5-5,5 l/sack
Paste density	1,65 Kg/l
Paste life	2 hours
Open time	20 minutes
Adjustment time	15 minutes
Adhesive strength under normal conditions	≥ 0,5 N/mm ²
Adhesive strength after water cycle	≥ 0,5 N/mm ²
Yield	single glue: 3-4 Kg/m ² double glue: 6-8 Kg/m ²

*Data based on tests carried out under normal laboratory conditions
23 ± 2°C and 50 ± 5%HR < 0.2 m/s*

NOTE

The recommendations for use are based on our own knowledge and experience. The technical data provided have been obtained under normal laboratory conditions, and may therefore vary according to the environmental conditions in the place where the product is used. As the application conditions are beyond our control, the information provided here does not imply that the company accepts responsibility for any variations.